SCIGIENE PRODUCT SELECTION GUIDE
Thermometer Guide

Thermometers. Thermocouple, Pocket, Infra Red etc.

Probes - standard & customized

Thermometers - Hand Held

Water Resistant

Thermocouple type Thermometers

TK0305 – Splash Proof, -50 to +1300C

Thermistor type Thermometers

TW-810960 Digital Alarm Thermometer

Waterproof

Thermocouple type Thermometers

TN806LCE Waterproof Dual Thermocouple/IR, -60C to +500C

TCT303F – Waterproof IR with built-in Probe

TCT013K Waterproof Mini type K, -64C to +1400C

TCT012 Waterproof Mini with built-in probe, -50C to +350C

Thermometers – Wall Mount

DTP-392 Digital Probe Cooking Thermometer

DTTC Combo Probe, Thermometer, Timer & Clock

DTP-482 Programmable Probe, Thermometer & Timer

TSP-572 Touch Screen Probe, Thermometer & Timer

PAT20 Alarm Thermometer

Pocket Thermometers Dial or Digital

Pocket dial Thermometers

PT0150 dual scale 32mm dial –10 to 110C/ -58 to 302 F

PT0110 25 mm dial, 10 to 300 C

PT0220 25 mm dial, 0 to 220 F

PT0160 25 mm dial, -40 to 160 F

PT0100 25 mm dial, -10 to 100 C

Digital Pocket Thermometers

PTP302 S. Steel Waterproof, -40 to +150 C, +/- 1.0C

PTQ450 S. Steel Quick Tip, Waterproof, -40 to +230C, +/- 0.5C

PT450B/R ProAccurate Quick Tip, Waterproof, -40 to +230°C, +/- 0.5C

PTQ2450 ProAccurate Quick Tip, Waterproof, -40 to +230C, +/- 0.5C

PDT302 F only, -40 to +302F

PT0314 waterproof stick type –50 to 150C

PT0363 Digital Waterproof Thermometer –10C to +200C

SPRH02 Thermo-Hygrometer Pen 5% to 95% RH

Infrared Thermometers

TN806LCE Waterproof Dual IR & Thermocouple, -60C To +500C

IR0375 Pocket IR Thermometer -55C to +220C

TN205L – IR Laser Thermometer, -55C to +250C

TN408LC – IR "Gun Style" IR Thermometer with optional probe, -60C to +500C.

TN40ALC "Gun Style" Laser IR Thermometer with optional probe, -60C to +760C

F140L – Food Grade IR Thermometer, -55C to +280C

TN400L Low Cost IR Thermometer, -50C to +400C

TCT303F – Waterproof IR Thermometer with built-in Probe, -55C to +250C.

TN002Ci – Mini IR w/pocket clip, -33C to +220C

TN425LE – Heavy Duty IR, 50:1 D:S Ratio, -60C to +1000C